Mobile Equipment Carriers

Knürr MetraMobil®

Page 20 to 27





Knürr MetraMobil® Strong points

Variability

- A completely individual cart can be configured from a basic frame in 2 heights, 3 colors and 5 module components.
- Ideal height adjustment with variable height setting of the shelves

• Stability

- High load rating: up to 600 N per worktop up to 2200 N for full trolley
- Distributed load drawer extension up to 100 N
- High stability with advanced sheet steel construction

Functionality

 Suitable for the most varied areas of application: PC or printer station, IT-cart, logistics or laboratory

• Cable management

- Safe cable routing with two cable ducts integrated in the extrusion
- Clear and orderly cable management with integration of accessory parts,
 e.g. a socket strip, which can be mounted on the extrusion.

• Well-thought out solutions

- Vision and contact protection provided by the easy "on-off" rear panel, no tools needed
- Orderly arrangement of small material with drawer module with removeable small parts tray
- Smooth running 3/4 pull-out "Quattro" guide

• ESD versions

 Safety and protection in demanding ESD environments provided by ESD castors and ESD powder coating.




MET 20000



MET00034







MET00037

Knürr MetraMobil® Basic Configurations

• Replace "x" with the number of your color choice.

Final digit of order number .1:

Worktops, RAL 7035, light grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black Final digit of order number .2:

Worktops, NCS 3060 R80B, blue Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .9:

Worktops, RAL 7016, anthracite grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

ESD versions: Note: ESD only in color variant .1 (light grey)

Final digit of order number .1:

Worktops, RAL 7035, antistatic light grey Extrusions, RAL 9006, white aluminum Handle: RAL 7021, dark grey, antistatic

Design your individual trolley as follows:

- 1. Select height of the basic trolley
- 2. Select ESD or standard model
- 3. Pick out additional modules
- The basic model can be easily expanded with system components (bear ESD in mind!)
- Worktops: set at any height

Dimensions

- Height, 900 mm or 1120 mm
- Full width, 550 mm
- Useful width, 500 mm
- Depth, 580 mm
- Useful depth, 440 mm
- Castor Ø 125 mm

Load rating

Basic rack:

2200 N

Per castor:

• 750 N

Surface load per worktop:

600 N

• Material/Finish

Basic rack consists of:

- Extrusions: extruded aluminium, powder-coated
- · Worktops: sheet steel, powder-coat textured

Handle:

· aluminium tube, powder-coat textured

Supply schedule, Basic Configuration

a. Height 900 mm

- 1 Basic rack
- 1 Worktop with handle
- 1 Worktop

b. Height 1120 mm

- 1 Basic rack
- 1 Worktop with handle
- 2 Worktops

• Supply schedule Metramobil Light

- 1 Basic rack
- 1 Worktop with handle

How supplied

• Modules for self installation

w	Н	D	w	d	Model	ESD	Order no.	UP
550	900	580	500	440			00.709.000.x	1 unit
550	900	580	500	440		•	00.709.100.1	1 unit
550	900	580	500	440	Metramobil light		00.709.200.x	1 unit
								1 unit
550	1120580		500	440			00.711.000.x	1 unit
550	1120580		500	440		•	00.711.100.1	1 unit
550	1120580		500	440	Metramobil light		00.711.200.x	1 unit



Metramobil Basic height 1120 mm

MET00018



Metramobil Basic height 900 mm

MET00014



Metramobil light

MET20008

Dimensions in mm: W = Width

H = Heiaht

D = Depth h = Installation height

unit, 1 HU = 44.45 mm 19"= 482.6 mm, (ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging d = Useful depth L = Length

ka = Weiaht

HU = Standard height

1 inch = 25,4 mm Conversion:

Replace "x" with the number of your color choice



Knürr MetraMobil® 900

 Replace "x" with the number of your color choice.

• Final digit of order number .1:

 Worktops, RAL 7035, light grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .2:

 Worktops, NCS 3060 R80B, blue Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .9:

- Worktops, RAL 7016, anthracite grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black
- Worktops: set at any height
- Castor: Ø 125 mm

Load rating

Basic rack:

2200 N

Per castor:

750 N

Surface load per worktop:

• 600 N

Material/Finish

Basic rack consists of:

- Extrusions: extruded aluminium, powder-coated
- Worktops: sheet steel, powder-coat textured

Handle:

· aluminium tube, powder-coat textured

Supply schedule

- 1 Basic rack
- 1 Worktop with handle
- 1 Worktop
- 1 Keyboard extension with mouse table

How supplied

· Modules for self installation



MET00058

W	Н	D	w	d	Order no.	UP
550	900	580	500	440	00.709.002.x	1 unit

Knürr MetraMobil® 1120

 Replace "x" with the number of your color choice.

• Final digit of order number .1:

- Worktops, RAL 7035, light grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black
 - Final digit of order number .2:
- Worktops, NCS 3060 R80B, blue Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .9:

- Worktops, RAL 7016, anthracite grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black
- Worktops: set at any height
- Castor: Ø 125 mm

Load rating

Basic rack:

2200 NPer castor:

• 750 N

Surface load per worktop:

• 600 N

Material/Finish

Basic rack consists of:

- Extrusions: extruded aluminium, powder-coated
- Worktops: sheet steel, powder-coat textured

Handle:

aluminium tube, powder-coat textured

Supply schedule

- 1 Basic rack
- 1 Worktop with handle
- 2 Worktops
- 1 Keyboard extension with mouse table

How supplied

Modules for self installation



MET00060

w	н	D	w	d	Order no.	UP
550	1120	580	500	440	00.711.002.x	1 unit

Knürr MetraMobil® 1120 with drawer module

• Replace "x" with the number of your color choice.

Final digit of order number .1:

• Worktops, RAL 7035, light grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .2:

 Worktops, NCS 3060 R80B, blue Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black

Final digit of order number .9:

- Worktops, RAL 7016, anthracite grey Extrusions, RAL 9006, white aluminium Handle, RAL 9011, graphite black
- Worktops: set at any height
- Castor: Ø 125 mm

Load rating

Basic rack:

• 2200 N

Per castor:

750 N

Surface load per worktop:

• 600 N

Material/Finish

Basic rack consists of:

- Extrusions: extruded aluminium, powder-coated
- Worktops: sheet steel, powder-coat textured

Handle:

• aluminium tube, powder-coat textured

Supply schedule

- 1 Basic rack
- 1 Worktop with handle
- 2 Worktops
- 1 Drawer module

How supplied

Modules for self installation



MET00017

W	Н	D	w	d	Order no.	UP
550	1120	580	500	440	00.711.004.x	1 unit

H = Height
D = Depth
h = Installation height

d = Useful depth L = Length

kg = Weight

HU = Standard height

unit, 1 HU = 44.45 mm 19"= 482.6 mm, (ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging

1 inch = 25,4 mm Conversion:

Replace "x" with the number of your color choice



Knürr MetraMobil® Worktop

- Replace "x" with the number of your color choice.
- Standard versions:

Final digit of order number .1:

RAL 7035 light grey

Final digit of order number .2:

NCS 3060 R80B, blue

Final digit of order number .9:

• RAL 7016 anthracite grey

ESD version: Note: ESD only in color variant .1 (light grey)

Final digit of order number .1: • RAL 7035 anti-static, light grey

- For storage and work purposes
- Variable setting between the vertical extrusions

ESD model in accordance with EN 100015

- Supply schedule
 - 1 Worktop
 - Mounting material
- How supplied

 - Flat-packed kit



w	Н	D	Model	ESD	Order no.	UP
500	25	440			00.701.020.x	1 unit
500	25	440		•	00.701.120.1	1 unit
500	25	440	with handle		00.701.021.x	1 unit
500	25	440	with handle	•	00.701.121.1	1 unit

Knürr MetraMobil® Anti-Slide Mat Set

Note:

Anti-slide mats are not possible at the same time with keyboard extension!

- Consists of 4 anti-slide mats
- For slide-proof storage of parts to be transported
- As scratch protection for the worktop
- Material
 - Industrial rubber, self-adhesive
- Color
 - Black

- · Supply schedule
 - 4 Anti-slide mats
- How supplied
 - Flat-packed kit

Antistatic version

- · Consisting of four anti-slip mats, antistatic, self-adhesive
- Material
 - Industrial rubber, antistatic
- Color
 - Black

w	H D	Antistatic	Order no.	UP
475	430		00.701.070.9	1 unit
475	430	•	00.701.170.9	1 unit



MET00040

Knürr MetraMobil® Keyboard Extension

- Replace "x" with the number of your color choice.
- Standard versions:
 - Final digit of order number .1:
 - RAL 7035 light grey
 - Final digit of order number .2:
 - NCS 3060 R80B, blue
 - Final digit of order number .9:
 - RAL 7016 anthracite grey
- **ESD** version:
 - Note: ESD only in color variant .1 (light grev)
 - Final digit of order number .1:
 - RAL 7035 anti-static, light grey

- $\bullet \quad$ For mounting on Knürr MetraMobil $\ensuremath{^{\circ}}$ worktop and worktop with handle
- With side mouse table, left/right
- Extension 200 mm

ESD model in accordance with EN 100015

- Supply schedule
 - 1 Keyboard extension
 - Mounting material
- How supplied
 - Flat-packed kit
- - With worktop with keyboard extension, an anti-slide mat is not possible!

w	Н	D	ESD Order no.	UP
505	45	200	00.701.060.x	1 unit
505	45	200	• 00.701.160.1	1 unit



Knürr MetraMobil® Drawer Module

- Replace "x" with the number of your color choice.
- Standard versions:
 - Final digit of order number .1:
 - RAL 7035 light grey
 - Final digit of order number .2:
 - NCS 3060 R80B, blue
 - Final digit of order number .9:
 - RAL 7016 anthracite grey
- ESD version: Note: ESD only in color variant .1 (light grey)
 - Final digit of order number .1:
 - RAL 7035 anti-static, light grey

- · For holding small material
- Including divider set
- Material/Finish
 - · Sheet steel, powder-coat textured

ESD model in accordance with EN 100015

- Supply schedule
 - 1 Drawer module
 - Mounting material
- · How supplied
 - Flat-packed kit

w	н	D	ESD Order no.	UP
500	165	440	00.701.001.x	1 unit
505	165	440	• 00.701.101.1	1 unit



MET00017

Dimensions in mm: W = Width

H = Height
D = Depth
h = Installation height

d = Useful depth L = Length

HU = Standard height

unit, 1 HU = 44.45 mm 19"= 482.6 mm, (ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging

ka = Weiaht

1 inch = 25,4 mm Conversion:

Replace "x" with the number of your color choice



Knürr MetraMobil® Rear Panel

- Replace "x" with the number of your color choice.
- Standard versions:

Final digit of order number .1:

RAL 7035 light grey

Final digit of order number .2:

NCS 3060 R80B, blue

Final digit of order number .9:

• RAL 7016 anthracite grey

ESD version:

Note: ESD only in color variant

.1 (light grey) Final digit of order number .1:

• RAL 7035 anti-static, light grey

- With cable entry
- ESD model in accordance with EN 100015
- Material/Finish
 - Sheet steel, powder-coat textured
- Supply schedule
 - 1 Rear panel
 - Mounting material
- How supplied
 - Flat-packed kit



MET00033

W	н	D	ESD	Order no.	UP
380	900			00.701.010.x	1 unit
380	1120			00.701.011.x	1 unit
380	900		•	00.701.110.1	1 unit
380	1120		•	00.701.111.1	1 unit

Knürr MetraMobil® Cable Management Set

- Consists of:
 - Di-Strip socket strip, 4-way, without switch
 - Strain relief
 - Two cable reel elements

- Supply schedule
 - 1 Cable management set
 - Mounting material
- How supplied
 - Flat-packed kit

Order no.	UP
00.701.050.1	1 unit



MET00037

Knürr MetraMobil® Castor Set

- Load rating, 750 N per castor, Ø 125 mm
- Color
 - RAL 9011, graphite black

- · Supply schedule
 - 4 smooth-running castors,
 - 2 with brake

ESD	Order no.	UP
	00.701.965.9	1 unit
•	00.128.975.9	1 unit



MET00021



knuerr-consoles.com | Knürr GmbH, Mariakirchener Straße 38, 94424 Arnstorf, Germany ID-Nr. DE 363797731

© 2024 Knürr GmbH. All rights reserved. Knürr* and the Knürr logo are trademarks or registered trademarks of Knürr GmbH. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness herein, Knürr GmbH assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.