

SEATING

205 to 214



CHAIRS

Description	Svenstol S5	Svenstol S6	Mr.24	Operator	RECARO Guard	RH Secur 24
Art.Nr.	00.350.098.1 00.350.098.9	00.350.099.1 00.350.099.9	00.350.073.9	00.350.031.9 + 00.350.035.9	00.350.072.9	00.350.078.9
Max. User Weight	150 kg (200 kg optional)	150 kg (200 kg optional)	200kg	150 kg	150kg	200 kg
Sliding Seat	Yes	Yes	Yes	Yes	Yes	optional
Seat Width	550 mm	550 mm	470 mm	495 mm	550 mm	410 mm
Seat Mechanism	activePlus mechanism with torsion spring	activePlus mechanism with torsion spring	Simiar mechanics	Simiar mechanics	Synchronous mechanism with spring force adjustment	Hardened steel block
Headrest	Height / tilt adjustable and 180° rotatable	Height / tilt adjustable and 180° rotatable	Height adjustable, genuine leather	Height adjustable, patent leather	Height- / tilt adjustable	Height- / tilt adjustable
Backrest	comfortPlus upholstery Angle to seat surface adjustable by 25 2 air chambers with hand pump, height adjustable adjustable Lean-to pressure	comfortPlus upholstery Angle to seat surface adjustable by 25 2 air chambers with hand pump, height adjustable adjustable Lean-to pressure	manually adjustable, with padding Height adjustable lumbar support adjustable backrest pressure	manually adjustable, with padding or mesh covering Height adjustable lumbar support adjustable backrest pressure	manually adjustable, with padding Double chamber lumbar support, height-adjustable adjustable backrest pressure	Lord can support parallel adjustable in height and depth Ergonomically shaped backrest
Armrest	Folding armrests with latching function	Folding armrests with latching function	3-D Adjustable, with softtouch surface	3-D Adjustable, with softtouch surface	folding armrests adjustable	foldable
Seat Cover	Partial leather / Climatex fabric 500,000 abrasion cycles	Full leather	Fabric (72% Cradura, 16% New Wool, 12% Cellulose) 150,000 scrubbing cycles	Fabric (72% Cradura, 16% New Wool, 12% Cellulose) 150,000 scrubbing cycles	synthetic leather / fabric 150,000 scrubbing cycles	synthetic leather / fabric 1 million scrubbing cycles
Lumbar Support	yes (2-chamber air system)	Ja (2-Kammer Luftsystem)	yes (height- and depth adjustable)	yes (height adjustable)	yes	yes
Seat Height Adjustment	440-650 mm	440-650 mm	420-520 mm	420-520 mm	420-520 mm	400-520 mm
Castors	Soft, for hard floors	Soft, for hard floors	Soft, for hard floors	Soft, for hard floors	Soft, for hard floors	Soft, for hard floors
Certificates	GS, British Standard, IGR	GS, British Standard, IGR	GS, British Standard, ANSI, AGR	GS, British Standard, ANSI, AGR	GS, British Standard	GS, British Standard

Dimensions in mm: W = Width
H = Height
D = Depth
h = Installation height
d = Useful depth
L = Length

HU = Standard height unit, 1 HU = 44.45 mm
19" = 482.6 mm,
(ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging
kg = Weight

Conversion: 1 inch = 25.4 mm
1 pound = 453.6 g

Replace „x“ with the number of your color choice

24/7

Svenstol S5

- Specially designed for control centre workstations, durable, ergonomic and resilient
- Highest seating comfort due to wide ergonomically shaped comfortPlus upholstery
- Headrest adjustable in height and rotated by 180
- Backrest inclination 0-25 degrees
- Folding armrests, quickly adjustable with latching function, can be folded back and adjusted in height by 6 cm
- Heavy-duty mechanism with free-swing function, seat tilt lockable, angular movement: -6° to +19
- Weight adjustment (back pressure) from 45-150 kg, load capacity GS and TÜV tested from 200 kg
- Extra strong gas spring for height adjustment with depth suspension
- Extra large base (72cm) with 6 arms for maximum stability (tilt-resistant)
- Dynamic and static sitting possible
- Pneumatic double-chamber lumbar support
- Soft castors for hard floors

- **Technical Data**
 - Backrest width and height 510 x 650 mm
 - Width and depth of seat 550 x 410 - 510 mm (10cm sliding seat)
 - Width and length of folding armrests 70 x 380 mm
 - Height adjustment range of headrest 0 - 170 mm
- **Material**
 - Cover types:
 - Fabric Climatex black 24/7 w. Leather headrest
 - Partial leather, Climatex black w. Leather headrest
 - Full leather (cowhide) black
- **Color**
 - Cover: Black
 - Seams: Black
 - Base: polished aluminium
- **Supply schedule**
 - 1 Svenstol S5 control centre chair
- **How supplied**
 - Assembled, in carton and/or on pallet
- **Please note:**
 - Hard castors can be ordered for soft floors (5-year full guarantee in 24/7 use)
 - Also available as version 150+, weight adjustment (back pressure) from 45-200 kg, load capacity GS and TÜV tested up to 230 kg



Model	Order no.	UP
Svenstol S5 control chair with folding armrests	00.350.098.1	1 unit
Svenstol S5 control chair with foldable and height-adjustable armrests	00.350.098.9	1 unit

24/7

Svenstol S6

- Specially designed for control centre workstations, durable, ergonomic and resilient
 - Highest seating comfort due to wide ergonomically shaped comfortPlus upholstery
 - Headrest adjustable in height and rotated by 180
 - Backrest inclination 0-25 degrees
 - Folding armrests, quickly adjustable with latching function, can be folded back and adjusted in height by 6 cm
 - Heavy-duty mechanism with free-swing function, seat tilt lockable, angular movement: -6° to +19
 - Weight adjustment (back pressure) from 45-150 kg, load capacity GS and TÜV tested from 200 kg
 - Extra strong gas spring for height adjustment with depth suspension
 - Extra large base (72cm) with 6 arms for maximum stability (tilt-resistant)
 - Dynamic and static sitting possible
 - Pneumatic double-chamber lumbar support
 - Soft castors for hard floors
- **Technical Data**
 - Backrest width and height 510 x 650 mm
 - Width and depth of seat 550 x 410 - 510 mm (10cm sliding seat)
 - Width and length of folding armrests 70 x 380 mm
 - Height adjustment range of headrest 0 - 170 mm
 - **Material**
 - Cover: Full leather (cowhide) black
 - **Color**
 - Black
 - Seams: Black
 - Base: polished aluminium
 - **Supply schedule**
 - 1 Svenstol S6 control centre chair
 - **How supplied**
 - Assembled, in carton and/or on pallet
 - **Please note:**
 - Hard castors can be ordered for soft floors (5-year full guarantee in 24/7 use)
 - Also available as version 150+, weight adjustment (back pressure) from 45-200 kg, load capacity GS and TÜV tested up to 230 kg



Model	Order no.	UP
Svenstol S6 control chair with folding armrests	00.350.099.1	1 unit
Svenstol S6 control chair with foldable and height-adjustable armrests	00.350.099.9	1 unit

Dimensions in mm:	W = Width	HU = Standard height
	H = Height	unit, 1 HU = 44.45 mm
	D = Depth	19" = 482.6 mm,
	h = Installation height	(ideal for 19" components
	d = Useful depth	in acc. with DIN 41494)
	L = Length	UP = Unit of packaging
		kg = Weight
Conversion:	1 inch = 25.4 mm	Replace „x“ with the number of
	1 pound = 453.6 g	your color choice

24/7

24/7 Control Room Chair Mr. 24

- Our top selling Control Room Chair
 - Generous seat and backrest for maximum comfort
 - Long backrest with integrated adjustable lumbar support, Similarmechnic opens up to 32° and stepless adjustment of back leaning angle Adjustable sliding seat allows for adaption to individual leg length
 - Height adjustable black leather head rest
 - Seat and back rest tilt synchronously to body movement
 - Individual main spring adjustment for different user weights
 - Permanent dorsal support also when leaning all the way back
 - Sedo-Lift-Mechanic for best cushioning also in lowest seating position
 - Extra robust arm rest for 24/7 use
 - Soft castors for hard surfaces
 - GS approved
 - British Standard approved
 - Seating width and depth: 470 x 400 mm
 - Height adjustment of head rest: 50 mm
 - Neck rest width and height: 360 x 150 mm
 - Similarmechnic suitable for up to persons of up to 200 kg / 440lbs.
 - Max. back rest tilt: 32°
- Seat height adjustment: 420 – 515 mm
 - Arm rest height adjustment: 190 – 300 mm
 - Arm rest width adjustment: 2 x 50 mm
 - Arm rest depth adjustment: 80 mm
- **Material**
 - Set 2G8 black 72%CraduraTM, 16% new wool, 12% Cellulose
 - 150.000 cycles (Martindale)
 - DIN EN 1021-1/2
- **Color**
 - Fabric: black
 - Castor base: black
- **Supply schedule**
 - 1 Control Room Chair
- **How supplied**
 - Pre assembled
- **Please note:**
 - Hard castors for carpet surfaces available
 - Many other configurations available on request



ACC20005

Model	Order no.	UP
Mr. 24h, black fabric, armrests, head rest	00.350.073.9	1 unit
Protective cover for head rest	00.350.074.9	1 unit

24/7 Control Room Chair Operator

- Proven Control Room Chair for dynamic seating
 - Suitable for users up to 150 kg / 325lbs.
 - Similarmechanic with heavy duty springs
 - Integrated sliding seat (seat depth adjustable 400 to 460 mm)
 - Comfortable, reinforced seat padding, Seating width max. 495 mm
 - Height adjustable lumbal support
 - Sedo-Lift-Mechanic (390 to 520 mm seat height),
 - Black aluminum cast castor base
 - Similarmechanic with adjustable springs
 - Back rest with padding or mesh covering
 - 3-D softtouch armrests
 - Height adjustable black leather head rest
 - Soft castors for hard surfaces
- **Material**
 - Set 2G8 black 72%CraduraTM, 16% new wool, 12% Cellulose
 - 150.000 cycles (Martindale)
 - DIN EN 1021-1/2
 - **Color**
 - Fabric: black
 - Castor base: black
 - **Supply schedule**
 - 1 Control Room Chair
 - **How supplied**
 - Pre assembled
 - **Please note:**
 - Hard castors for carpet surfaces available
 - Many other configurations available on request



ACC20006

Model	Order no.	UP
Operator 24/7, mesh covering backrest, arm rests, head rest	00.350.031.9	1 unit
Operator 24/7, padding backrest, arm rests, head rest	00.350.035.9	1 unit



ACC20052

Provided for use with the kind permission of Sedus Stoll AG.
Unauthorised use is prohibited.

Dimensions in mm: W = Width
H = Height
D = Depth
h = Installation height
d = Useful depth
L = Length

HU = Standard height unit, 1 HU = 44.45 mm
19" = 482.6 mm, (ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging
kg = Weight

Conversion: 1 inch = 25,4 mm
1 pound = 453,6 g

Replace „x“ with the number of your color choice

24/7
Control Room Chair – Swivel Chair 24/7 RECARO

- For 24/7 use in Control and Surveillance Rooms, Emergency Centers and ATC/ATM
- Height adjustable and tiltable head rest
- Double chamber lumbar support
- Frame and padding made from heavy duty materials
- Tiltable flip-up arm rests
- Tested for maximum load
- Ambidextrous handle for backrest angle
- Ergonomic padding for maximum seating comfort
- Heavy duty Free Tilt mechanism, lockable in 3 positions
- Individually adjustable to user weight (ca. 60 - 150 kg / 130 - 330 lbs.)
- Extra strong gas spring for height adjustment
- Extra large castor base for best stability
- Adjustable thigh support
- Soft castors for hard surfaces
- GS certified
- British Standard

• Technical Data

- Width and height of backrest 520 x 620 mm
- Width and depth of seat 550 x 560 mm
- Width and depth of arm rests 74 x 324 mm
- Height adjustment of headrest 0 - 80 mm
- Tilting of headrest 0 - 35°

• Material

- Seat and backrest: Synthetic leather

• Color

- Fabric / leather: Black
- Castor base: Polished aluminum

• Supply schedule

- 1 Control Room Swivel Chair 24/7 RECARO
- 1 Protective Cover for head rest

• How supplied

- Assembled

• Please note:

- Hard castors for carpet surfaces available



ACC20003



ACC20051

Model	Order no.	UP
Control Room Chair 24/7 RECARO Guard	00.350.072.1	1 unit

24/7

Control Room Chair RH Secur 24 24/7, headrest, Flip UP armrests

- Comfortably cut seat from the automotive industry
 - Without gimbal extension
 - 2 way mechanical lumbar support
 - Flip up armrests
 - Soft castors for hard floors
 - Supportive and adjustable headrest
 - Ergonomically shaped backrest
 - Lordosis support parallel adjustable in height and depth
 - Extra thick seat cushion
 - Stable and robust tilt mechanism for dynamic sitting
 - Controls for right- and left-handers
- **Technical data**
 - Seat width 410 mm
 - Seat depth 435 mm
 - Backrest width 481 mm
 - Backrest height 829 mm
 - **Material/Color**
 - Leather cover (BC 12/automotive/imitation leather) in combination with Staccato black fabric with 1,000,000 Martindale abrasion tests.
 - Foot frame in polished aluminium
 - **Supply schedule**
 - 1 Control Room Chair
 - **How supplied**
 - Pre assembled
 - **Note**

Many other equipment options

 - Hard castors for soft floors
 - Other covers on request
 - Protective cover for headrest
 - 6-way comfort headrest
 - Seat depth adjustment 12 cm
 - Various armrests
 - Optionally with seat depth adjustment



ACC20000

Type	Model	Order no.	UP
RH SECUR 24	With Flip UP armrests	00.350.078.9	1 unit

Dimensions in mm: W = Width
H = Height
D = Depth
h = Installation height
d = Useful depth
L = Length

HU = Standard height unit, 1 HU = 44.45 mm
19" = 482.6 mm,
(ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging
kg = Weight

Conversion: 1 inch = 25.4 mm
1 pound = 453.6 g

Replace „x“ with the number of your color choice

Professional

se:do

se:do's special features include ergonomic functions that are easy to adjust, ensuring that alternating users will always have a healthy and comfortable sitting posture. se:do has an ergonomically formed seat pan and a height-adjustable backrest with a wide opening angle, which provides maximum back support in all positions. The Sedus "similar" mechanism allows the seat and backrest to always move in sync with the body. Numerous adjustment options round off the ergonomic properties, making every user feel relaxed and comfortable – up to 130kg of body weight.

- Backrest pressure finely graduated adjustable
- Integrated adjustable lumbar support (80mm)
- Height-adjustable tall backrest (610 – 690 mm)
- Backrest width 465 mm
- Height-adjustable plastic armrests (190 – 290 mm), clear span 490 – 510 mm (dependent on model)
- Robust five-wheel plastic base
- "Similar" mechanism with spring tension quick adjustment
- Gas spring with mechanical depth suspension
- Sliding seat (with 60 mm depth adjustment, dependent on model)
- Adjustable seat inclination (4°)
- Backrest comfortably upholstered or with breathable membrane cover
- Soft castors for hard floors

Also available in a conductive version for ESD workstations.

• Material

- Fabric wool Fame F60999 black 200.000 abrasion runs according to Martindale DIN 4102:B2 normal flammability (Cushion)
- Self-supporting knitted Polyester (membrane)
- ESD version: Gaja anti-static black 2A1 100% new wool 50.0000 abrasion runs according to Martindale DIN 4102:B2 normal flammability
- Five-wheel plastic base: black

• Certificates

- GS Safety label of TÜV Rheinland LGA products GmbH / DIN EN 1335
- Ergonomics certificate of TÜV Rheinland LGA Products GmbH
- Tested for harmful substances by TÜV Rheinland LGA Products GmbH
- Quality Office certificate
- AGR certificate
- 5 year warranty

• Supply schedule

- 1x swivel chair

• Note

Available upon request:

- Hard castors for soft floors
- Additional versions and covers



se:do Membrane, with armrests

ACC20007



se:do Cushion, with armrests

ACC20008



se:do also ESD version available

ACC20009

Type	Model	Order no.	UP
Swivel chair se:do	Membrane, without armrests	00.350.061.9	1 unit
Swivel chair se:do	Membrane, with armrests	00.350.062.9	1 unit
Swivel chair se:do	Cusion, without armrests	00.350.063.9	1 unit
Swivel chair se:do	Cushion, with armrests	00.350.064.9	1 unit
Swivel chair se:do	Cushion, without armrests, ESD	00.350.065.9	1 unit
Swivel chair se:do	Cushion, wit armrests, ESD	00.350.066.9	1 unit

Meeting

Visitor's Chairs

- Aesthetic visitor's chair for conference rooms and reception areas
 - Stackable
 - Black cantilever frame
 - Robust Ø 25 mm / 1" steel pipe
 - Plastic skids
 - Plastic arm rests
- **Material**
 - Set 2G8 black 72%CraduraTM, 16% new wool, 12% Cellulose
 - 150.000 cycles (Martindale)
 - DIN EN 1021-1/2
 - **Color**
 - Fabric: black
 - Cantilever frame: black
 - **Supply schedule**
 - 1 Visitor's Chair
 - **How supplied**
 - Pre assembled
 - **Please note:**
 - Felt skids are available for glossy surfaces
 - Many other configurations available on request

Model	Order no.	UP
Black dot Cantilever with armrests, stackable, black	00.350.032.9	1 unit
Visitor chair (4-leg) without armrests	00.350.037.9	1 unit



ACC20012



ACC20053

Provided for use with the kind permission of Sedus Stoll AG.
Unauthorised use is prohibited.

Dimensions in mm: W = Width
H = Height
D = Depth
h = Installation height
d = Useful depth
L = Length

HU = Standard height unit, 1 HU = 44.45 mm
19" = 482.6 mm,
(ideal for 19" components in acc. with DIN 41494)
UP = Unit of packaging
kg = Weight

Conversion: 1 inch = 25,4 mm
1 pound = 453,6 g

Replace „x“ with the number of your color choice



knürr
World of control rooms

knuerr-consoles.com | Knürr GmbH, Mariakirchener Straße 38, 94424 Arnstorf, Germany ID-Nr. DE 363797731

© 2024 Knürr GmbH. All rights reserved. Knürr® and the Knürr logo are trademarks or registered trademarks of Knürr GmbH. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness herein, Knürr GmbH assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.